



Front and side rotary



Side flail



Transport mode

Introducing the revolutionary MowerMax™ Flail/Rotary Mowers - designed and purpose-built from the ground up to be far superior to the antiquated tractor-mounted flail & rotary mowers!



The MowerMax™ has a hydrostatic drive with infinite speeds from 0-20 mph, all wheel drive with industrial tires and forward, both or crab steering. The hydraulic system provides power to drive the vehicle as well as to power the cutter head and control hydraulics. A rear mounted 100 hp Perkins diesel engine provides plenty of power for this application.

- **INCOMPARABLE VISIBILITY** - The cab forward design greatly enhances operator's visibility making for a much better cutting experience.
- **OPTIMUM STABILITY** - The low center of gravity, axle stabilizer system and the industrial tires make it an extraordinarily stable machine.
- **OUTSTANDING MANEUVERABILITY** - 4 wheel steering with 3 steering modes allows the MowerMax™ to be extremely maneuverable and productive.
- **EXTREMELY COMPACT** - Allows for legal transport width in stow and much safer to travel in urban areas.
- **EXCEPTIONALLY SAFE** - The above characteristics & features make for a safer cutting, travel and transport experience.

Call for a demonstration or check us out online for more information, pictures and video!

813-781-0100 • www.mowermax.com • 813-781-1888



Side flail



Transport mode



Easily attach many other implements




Easy access




The MowerMax™ Flail & Rotary Mower is a transformative mowing machine with simple joystick controls, a tilt steering wheel, a plush, air-ride seat with tilt & lumbar and an Infinity stereo with Blue Tooth!




And the MowerMax™ Flail & Rotary Mower features 3 steering modes making it an extremely versatile and capable mower in all terrains!



4-WHEEL



FRONT



CRAB

MOWERMAX FLAIL / ROTARY SPECIFICATIONS

Mower Specifications

Front Flail Width	88 in.
Side Flail Width	62 in. & 74 in.
Front Rotary	90 in.
Side Rotary	60 in.
Flail Cutting Ability	Up to 1 in. Diameter Material
Rotary Cutting Ability	Up to 4 in. Diameter Material
Flail Drive	Belt-drive Hydraulic Bent Axis Motor
Rotary Drive	Direct-drive Hydraulic Bent Axis Motor
Mower Discharge Safety Shielding	Heavy Duty Rubber Belt
Anti-Scalp Features	Roller & Skid Shoes (Flail) & Skid Shoes (Rotary)

Power Unit Specs

Engine (all Tier III)	100HP 4.4L Turbo Diesel Perkins
Cooling System (engine & hydraulic)	Remote Radiator/Oil Cooler With High Flow Fan and Reversing Clean Out System
Transmission	Joystick Controlled Closed Loop Hydrostatic
Drive Train	Permanent 4-Wheel Drive & 4-Wheel Steering With 3 Steering Modes Fixed Front Axle & Oscillating Rear Axle
Differential	45% Limited Slip on Front Axle
Parking Brake	Standard, Electric Over Hydraulic
Service Brake	Standard
Tires	(4) 15-19.5, 14 Ply With All Purpose Tread
Ground Speed	Work Mode 0-5 MPH Travel Mode 0-20 MPH

General Specs

Length	Approximately 260 in. With 90" Rotary
Width	Approximately 82 in. Without Any Mowers
Height	102 in.
Weight (approximate)	12,500 lbs
Fuel Tank Capacity	30 gal

Features

- Cab and Safety Features:** Low profile suspension seats with lumbar and adjustable tilt as well as a seatbelt with an operator presence switch.
Easy to view gauge panel with a tachometer, water temperature, oil pressure, volt meter, fuel gauge and hour meter.
Two cup holders and a 12v power outlet for mobile phone or MP3 player.
Two forward work lights and one rear work light.
Six total amber flashing beacons: two forward, two rear and two on side of the cab as well as DOT reflector tape.
ROPS certification.
Clearview steering column with an adjustable tilt steering wheel and steering knob.
- Warranty:** One year limited warranty from MowerMax Equipment Co. and some components have an additional manufacturer's warranty.